



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

"We manufacture high quality acoustic products at affordable prices."

Noise control made easy!

- Acoustic products & supplies
- Isolation Booths & Custom manufacturing of sound booths, boxes, barriers, acoustic foam, panel systems, & more.
- Large & small projects welcome.

*When you buy a sound booth from us, you can **Trust** that you are getting the **best & most effective** sound isolation from a portable booth your money can buy."*

We are one of the **leaders the industry**, for innovative custom crafted sound isolation booths & noise control systems.

"We are the ones the others are trying to catch up to!"

Sound Isolation Booth

We use exclusive "State of the Art" materials!

This means our booths are lighter in over all weight, but have more than twice the sound reduction than most other booths in its class!

Exclusive Features:

- Compression door sealing system
- Heavy duty cam door closure
- Low profile ventilation systems
- Easy connector channels
- No hardware or extra parts required on most booths
- Quick & easy assembly
- Simple design & elegant look.
- Wide range of sizes & styles
- Modular & Highly Portable
- Portable units make repetitive assembly & disassembly a snap!
- Professional Results!
- Can customize to meet your specifications
- Professional Standardized Test results and Government test results for "Real" sound reduction numbers.



Applications for Isolation Booths:

- Recording
- Music/Band practice
- Voiceovers
- Broadcasting
- Industrial testing
- Quiet loud machinery
- Industrial Projects
- Private Conferences
- Cell Phone Booths
- Software Audio
- Hearing Testing
- Audiometric Booth
- Laboratories
- Language studies
- Karaoke
- Sound testing
- Trade Shows
- Language Studies
- Interpretation Booths
- Libraries
- Manufacturing
- Government & Military
- And more!



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

Economy Model:

This model does NOT come with lighting, window or ventilation system.

The economy model booth is great for those on a budget and not needing a loaded package. But keep in mind that our booths fit together so tightly that sound leakage is not a problem, but that also mean no air can get in or out. So if a person is going to be inside the booth for more than 15 minutes at a time, we highly recommend you add a ventilation system to this booth.

The Economy Model booth is basically the same booth as the Standard model having some of the best sound isolation available on the market it is just a bare bones package. Upgrades and additional options are available.

4' x 4' x 7' 2" - \$1,988

4' x 6' x 7' 2" - \$2,488

4' x 8' x 7' 2" - \$2,988

6' x 6' x 7' 2" - \$3,488

6' x 8' x 7' 2" - \$4,288

8' x 8' x 7' 2" - \$4,988

**Low Profile Ventilation System
and fan kits can be added.
Window(s) and light(s) can also be added.**

Exterior: Acoustic Fabric. Basic colors: Charcoal, Heather Grey, Silver, or Black. Other custom colors available -Ask

Interior: 2" thick, Charcoal Polyurethane Acoustic Foam one two walls and the ceiling.

Floor: Grey Acoustic Carpet

Walls: 3.25" total wall thickness

Connectors: Heavy Duty, Connector Channels.

Once assemble, the booth is very strong and sturdy.

Accessories: Exclusive Compression Door Seal System, Cam door closure system, 3" cable passage tube.

Custom Features: Anything is possible! Ask

Standard Models:

Standard Models are modular, & overall weight is fairly heavy, but not unreasonable.

Excellent Choice for those wanting modular booths but in a more permanent situation, where moving it will only be once and a while. Starting Weights at 650 lbs and up.

The Standard Model is a discounted package deal that saves you money because it includes most of the basic accessories including: a 1'x2' window in the door, ventilation system, "silent" interior florescent lighting. Other additional options and features can be added on for additional fees.

NIC Rating (average reduction): 32

Hertz range tested: 100-4000

One of the best ratings in the industry, in its class!

4' x 4' x 7' 2" - \$2,988

4' x 6' x 7' 2" - \$3,488

4' x 8' x 7' 2" - \$3,988

6' x 6' x 7' 2" - \$4,488

6' x 8' x 7' 2" - \$5,288

8' x 8' x 7' 2" - \$5,988

**Other Sizes Available
Standard Booths Can Be Manufactured
to Custom Sizes and Specifications.**

Exterior: Acoustic Fabric. Basic colors: Charcoal, Heather Grey, Silver, or Black.

Other custom colors available -Ask

Interior: 2" thick, Charcoal Polyurethane Acoustic Foam.

Other custom acoustic foam colors available -Ask

Floor: Grey Acoustic Carpet

Walls: 3.25" total wall thickness

Connectors: Heavy Duty, Connector Channels.

Once assemble, the booth is very strong and sturdy.

Accessories: 1'x2' window in door, Ventilation System, "Silent" Interior Florescent Light, Exclusive Compression Door Seal System, Cam door closure system, and 3" cable passage tubes.

Custom Features: Anything is possible! Ask

Premium Models:

Premium Models are modular and 25% lighter in overall weight than the standard model.

Even though the booth is lighter in over all weight, the wall panels are thicker so this booth does not lose its sound isolation integrity.

The Premium Model is a more portable solution for those needing modular sound isolation booths that will be regularly moving or transporting the booth. Starting Weights at 500 lbs +

The Premium Model is a complete package that comes with a 1'x2' window in the door, a ventilation system, and interior lighting. Additional options and features can be added at an additional fee.

NIC Rating: 30 (average reduction)

Hertz range tested: 100 - 4K

4' x 4' x 7' 2" - \$3,988

4' x 6' x 7' 2" - \$4,488

4' x 8' x 7' 2" - \$4,988

6' x 6' x 7' 2" - \$5,488

6' x 8' x 7' 2" - \$6,288

8' x 8' x 7' 2" - \$6,988

**Other Sizes Available
Standard Booths Can Be Manufactured
to Custom Sizes and Specifications**

Exterior: Acoustic Fabric. Basic colors:

Charcoal, Heather Grey, Silver, or Black

Other custom colors available - Ask

Interior: 2" thick, Charcoal Polyurethane Acoustic Foam.

Other custom acoustic foam colors available -Ask

Floor: Grey Acoustic Carpet

Walls: 3.75" total wall thickness

Connectors: Heavy Duty, Connector Channels.

Accessories: 1'x2' window in door, Ventilation system,

"Silent" Florescent Light, Exclusive Compression door

seal system, Cam door closure system and 3" cable passage tubes. Custom Features: Anything is possible! Ask

The data published above reflects the average with a tolerance of +/- 3 dB.

Sound Isolation booths help to reduce noise volume. They are not "Sound proof".



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

Remember:

We can customize the Shape & Size of your sound isolation booth/box, including Door Width and Location. We can also add additional windows, change location of windows, additional lights, increase Ventilation CFM (air) output, choose different Interior acoustic foam colors, and Exterior fabric colors. We can custom manufacture special wall configurations or anything else you require, to fit your noise reduction needs.

**Don't be afraid to ask, customizing may be less expensive than you think!
Call Us Toll Free: 1-888-833-1554**

Ask about our extra options and special order features for booths:

- Additional windows in assorted sizes
- Additional "Silent" Florescent lights
- Higher attenuation options for windows
- Additional cable passage tubes or access ports
- Magnetic door closure system with double door seals
- Additional doors, custom door sizes, or latching systems.
- Wide range of Exterior fabric colors
- Interior acoustic foam colors and patterns
- Additional or custom ventilation systems, and instillation locations
- Remote control for ventilation system fans
- Additional interior lights
- Custom Jack Panels (including .25" jacks, XLR, and more).
- Rubber isolation mats
- Castor wheel base
- and more!

Remember:

We can customize your booth to meet your specifications!
Including customizing any booths size, shape or height to meet your needs.

We can build Portable Sound Booths that are Extremely Large to Extremely Small. We can customize just about anything! Interior, Exterior, Heights, Doors, Access Panels, Ventilation Systems, and much more!

Upgrade to "Deluxe" or "Double Deluxe" and increase the sound reduction 6-12 decibels to ANY Booth.

Even wild and crazy booths like these:





1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

What You Get:	What Your booth Comes with:
<ul style="list-style-type: none"> * Superb Quality & Excellent workmanship. * One of the highest, most effective sound reduction ratings on the market, in its class! * Simple Design. * No hidden fees or costs. * Ventilation systems custom made to fit each booth size at no extra charge. * Honest Answers & time lines. "We want your trust & loyalty, not just your business". * Use the latest State-of-the-art materials, exclusively manufactured by Gretch-Ken Industries, Inc. * Hand crafted custom work, to meet your specifications. * NO extra hardware or parts required for assembly of smaller booths. * Tight seams and corners. "No need to hide gaps, when there's not any". * Sturdy solid structure. * Modular & portable panels. One of the only truly "Portable" booths on the market! * Lots of extra options to pick from to customize your booth. * We can build any booth to meet your specifications. * Knowledgeable staff, that keeps up with the latest technology. * Real sound reduction Ratings and Numbers, that is accurate. 	<ul style="list-style-type: none"> * Flush Door with heavy duty Cam Door closure system. * Customizable doors, door sizes, handle types, and closure systems. * Compression door seal for optimal prevention of sound leakage. * Sound Deadening Window(s) – We have one of the only windows in the industry with the highest STC Rating on the market! * Internal Lighting – One of the only florescent lights that are completely quiet! These lights have state-of-the-art electronic ballast. Gretch-Ken Industries, Inc. is the only one in the industry to have these lights in their booths. * 3" Cable passage tubes – your choice of locations. * Low profile, pre-attached ventilation system to fit your booth size, so no need to order extra ventilation systems. Your choice of location. Low Noise fan 29 dBA * No hardware or extra parts needed for assembly of most booths! * No sound leaking gaps between panels, or extra parts to hide gaps like with other booths. * One of the BEST Standardized Sound Reduction Test Results and one of the only government tested booths with one of the highest NIC ratings in the industry. Which means, you get solid sound stopping results. * We use "State-of-the-Art" materials. So you get <u>more than twice</u> the sound reduction than most other booths in its class! * Your choice of Exterior Fabric colors in a wide range of colors * Choices of Interior foam colors. * Expertly Engineered for Superior Performance. * Quality, "Hand Crafted" workmanship! * Professional look and Results!



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

Specifications for "Economy Model" Isolation Booth Comes Standard with: 3" Cable Passage Tube, Compression Door Seal System, Cam Closure.															
Dimensions:	4' x 4' x 7' 2" high														
Interior:	Walls & Ceiling covered in 2" thick Charcoal polyurethane acoustic foam on two walls and the ceiling. Floor carpeted with a gray, short loop pile carpet.														
Exterior:	½" thick, Charcoal acoustic fabric covering.														
Wall Thickness:	1 ¼" thick high-density wall with 2" acoustic polyurethane foam. Total wall thickness 3 ¼"														
Connectors:	Exclusive channel connector strips (no bolts, screws or tools required). Panels slip tightly into channel connector strips.														
Door:	27" x 72" Door with our exclusive low profile compression seal system & cam door closure system. "New" Floor Level doors, No step over.														
Cable Passage:	One 3" diameter cable passage tube sealed with acoustic foam														
Weight:	Starting weight 800 lbs. & up														
Assembly time:	Approximately 20 minutes based on 4'x4' (Assembly time may vary)														
Standardized Sound Reduction Test: <table border="1"> <tr> <td>Frequency (Hertz):</td> <td>125</td> <td>250</td> <td>500</td> <td>1000</td> <td>2000</td> <td>4000</td> </tr> <tr> <td>Reduction (dB):</td> <td>30</td> <td>31</td> <td>34</td> <td>41</td> <td>45</td> <td>47</td> </tr> </table>		Frequency (Hertz):	125	250	500	1000	2000	4000	Reduction (dB):	30	31	34	41	45	47
Frequency (Hertz):	125	250	500	1000	2000	4000									
Reduction (dB):	30	31	34	41	45	47									



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

Specifications for "Standard Model" Isolation Booth Specification Based on 4' x 4 Sound Isolation Booth Comes Standard with: 1'x2' Window in door, Compression Door Seal System, Cam door closure, Ventilation System, 3" Cable Passage Tube, Interior Light.		
Dimensions:	Basic sizes start at 4'x4' & up. Standard height 7'-2"	Custom booth sizes & shapes available. Larger & smaller. Extended heights also possible. Custom finishes - ASK.
Interior:	Walls & Ceiling covered in 2" thick Charcoal polyurethane acoustic foam (class 2). Floor carpeted with a grey, short pile carpet.	Fabric covered mounts attached to ceiling for lights or microphone mounts. Other foam colors, types, and patterns available as custom special orders.
Exterior:	½" thick Charcoal acoustic fabric.	Extra option: Charcoal, Black, Heather Grey, or Silver. Special Order: other acoustic fabric colors, or fire rated fabrics
Wall Thickness:	1 ½" thick high-density wall with 2" acoustic polyurethane foam. Total wall thickness 3 ¾"	Custom wall thickness available to meet any specifications. Including double wall systems & SoundBlocker composite walls.
Connectors:	Exclusive channel connectors (no bolts, screws or tools required for smaller booth sizes). Panels slip easily & tightly into channel connector strips.	Custom connector channels can be manufactured to meet your specifications.
Window(s):	Standard booths packages come with 1' x 2' Window in door, with five-layer insulation: 3/16" laminated glass, 1/2" Argon filled air space with rubber isolator, 1/4" glass, 7/8" air space, plus 1/8" Acrylic pane.	Extra options: 1'x2', 2'x2', 2'x3' or 3'x3', window can be added to most booths. Other window sizes can be special ordered. Such as: 1'x3', 1'x4', 2'x4', or 3'x4' and other sizes.
Door:	27" x 72" Door with our exclusive low profile compression seal system & cam door closure. "New" Floor Level doors, No step over.	Custom door sizes & placements can be arranged. Additional doors and be added as an extra option. 36" Handicapped accessible door options also available.
Ventilation:	50 CFM and up, air circulation fan, UL approved, 110 volt, with low acoustical noise rating, circulating air through a low profile sound muffling baffle system pre-attached to exterior of isolation booth. "New" now comes Standard with our new Low Noise 29 dBa Fan.	Fan CFM's and number of ventilation systems are predetermined to fit each booth size. Additional ventilation systems can be purchased. International Fan and cord kits available. "New" Low Noise Fans available – Lowest noise rating than ever before! Rated at 29dBa (two fan vent system is rated at 39 dBa)
Interior Light;	UL Approved, 110/220 volt. "Silent" interior florescent light.	Exclusive, Electronic Ballast "Silent" Florescent light. This handsome Low profile ceiling unit has two florescent bulbs & light cover. 110/220 volt. Comes with cord & on/off switch.
Cable Passage:	One 3" diameter cable passage tube sealed with acoustic foam.	Additional cable passage tubes or access ports can be added to each booth, including your choice of location(s). Custom Jack panels with ¼" & ½" Head phone Jacks, Stereo plugs, and/or XLR Jacks.
Weight:	Starting weight 950 lbs. & up	
Assembly time:	Approximately 20 minutes based on 4'x4'	Assembly time may vary
The 'Standard' model can outperform most other Isolation booths in its class with an astounding: NIC (Noise Isolation Class) rating of 32.		Standardized Sound Reduction Test Freq. (Hertz): 125 250 500 1000 2000 4000 Reduction (dB): 30 31 34 41 45 47



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

Specifications for "Premium Model" Isolation Booth Specification Based on 4' x 4 Sound Isolation Booth Comes Standard with: 1'x2' Window in door, Compression Door Seal System, Cam door closure, Ventilation System, 3" Cable Passage Tube, Interior Light.		
Dimensions:	Basic sizes start at 4'x4' & up. Standard height 7'-2"	Custom booth sizes & shapes available. Larger & smaller. Extended heights also possible. Custom finishes - ASK.
Interior:	Walls & Ceiling covered in 2" thick Charcoal polyurethane acoustic foam (class 2). Floor carpeted with a grey, short pile carpet.	Fabric covered mounts attached to ceiling for lights or microphone mounts. Other foam colors, types, and patterns available as custom special orders.
Exterior:	½" thick Charcoal acoustic fabric.	Extra option: Charcoal, Black, Heather Grey, or Silver. Special Order: other acoustic fabric colors, or fire rated fabrics
Wall Thickness:	1½" thick high-density wall with 2" acoustic polyurethane foam. Total wall thickness 3 ¾"	Custom wall thickness available to meet any specifications. Including double wall systems & SoundBlocker composite walls.
Connectors:	Exclusive channel connectors (no bolts, screws or tools required for smaller booth sizes). Panels slip easily & tightly into channel connector strips.	Custom connector channels can be manufactured to meet your specifications.
Window(s):	Standard booths packages come with 1' x 2' Window in door, with five-layer insulation: 3/16" laminated glass, 1/2" Argon filled air space with rubber isolator, 1/4" glass, 7/8" air space, plus 1/8" Acrylic pane.	Extra options: 1'x2', 2'x2', 2'x3' or 3'x3', window can be added to most booths. Other window sizes can be special ordered. Such as: 1'x3', 1'x4', 2'x4', or 3'x4' and other sizes.
Door:	27" x 72" Door with our exclusive low profile compression seal system & cam door closure. "New" Floor Level doors, No step over.	Custom door sizes & placements can be arranged. Additional doors and be added as an extra option. 36" Handicapped accessible door options also available.
Ventilation:	50 CFM and up, air circulation fan, UL approved, 110 volt, with low acoustical noise rating, circulating air through a low profile sound muffling baffle system pre-attached to exterior of isolation booth. "New" now comes Standard with our new Low Noise 29 dBa Fan.	Fan CFM's and number of ventilation systems are predetermined to fit each booth size. Additional ventilation systems can be purchased. International Fan and cord kits available. "New" Low Noise Fans available – Lowest noise rating than ever before! Rated at 29dBa (two fan vent system is rated at 39 dBa)
Interior Light;	UL Approved, 110/220 volt. "Silent" interior florescent light.	Exclusive, Electronic Ballast "Silent" Florescent light. This handsome Low profile ceiling unit has two florescent bulbs & light cover. 110/220 volt. Comes with cord & on/off switch.
Cable Passage:	One 3" diameter cable passage tube sealed with acoustic foam.	Additional cable passage tubes or access ports can be added to each booth, including your choice of location(s). Custom Jack panels with ¼" & ½" Head phone Jacks, Stereo plugs, and/or XLR Jacks.
Weight:	Starting weight 900 lbs. & up	
Assembly time:	Approximately 20 minutes based on 4'x4'	Assembly time may vary
NIC (Noise Isolation Class) rating of 30.		Standardized Sound Reduction Test Freq. (Hertz): 125 250 500 1000 2000 4000 Reduction (dB): 27 29 30 33 39 45



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608

We are proud to serve you with our superior personal service, quality hand craftsmanship, & some of the finest acoustic products on the market today!

ONE YEAR WARRANTY & INFORMATION

Gretch-Ken Industries, Inc. will warranty all acoustic products and sound Isolation booths manufactured by Gretch-Ken Industries, Inc. for one year from date of purchase. Gretch-Ken Industries, Inc. will repair or replace, at its factory, any part that may prove to be defective in materials or workmanship. All shipping costs are the responsibility of the purchaser. This warranty does not cover damage resulting from mishandling, vandalism, misuse, abuse, alteration, or lack of reasonable care. This includes damage resulting from outdoor use. All Gretch-Ken Industries, Inc. products are designed for indoor use only. All acoustic products are not 100% sound proof. Compliance with local and national building codes is purchaser's responsibility.

The above described warranty is extended to the original owner only and is not transferable.



Wire Transfers and Certified Checks Accepted

Financing option available for businesses

For more information or to make an order:

Call Toll Free: 1-888-833-1554

Sales Office Phone: 541-947-2602

Office hours 7:00am - 4pm

Pacific Standard Time (West Coast USA) - Monday through Friday

Fax: 541-947-2608

e-mail: sales@gretchken.com



1350 South M Street, Lakeview, OR 97630 ♦ sales@gretchken.com ♦ Phone: 541-947-2602 Fax: 541-947-2608



We manufacture Sound Isolation Booths and Enclosures.

- Designed for easy breakdown and assembly (no tools or hardware required)
- Superior sound isolation, one of the highest NIC ratings on the market!
- Full line of professional booth models, also custom models available
- Wide variety of standard sizes, also custom size capabilities
- Custom projects, not a problem.

We can custom manufacture sound Isolation booths to meet your specification.

For more pictures and information check us out on the web:

www.gretchken.com